

شركة
المنبع الشامل
للتجارة



LEISTER



We know how...

APPLICATIONS

ROOFING



CIVIL ENGINEERING



TECHNICAL TEXTILES



PLASTIC FABRICATION



FLOORING



TESTING



TRIAK ST

- › Professional heat gun weighing less than 1 kg (2.18 lbs)
- › Robust heat gun – made in Switzerland
- › Ergonomic, two-component handle
- › Developed for tough construction site use



Civil Kit



Flooring Kit

Fusion 3C

- › Up to 3.6 kg/h (8 lbs/h) output volume
- › A surprisingly compact, handheld extrusion welder
- › Robustly design
- › Adjustment extrusion volume
- › Various holding options



Geostar G7

- › It is optimized for underground engineering, landfills and mines
- › At welding speeds up to 12 m/min
- › single-hand operation
- › Display of the welding parameters and voltage



Twinny T5

- › Digital display shows speed and temperature
- › Mechanical over pressure protection
- › Welding speed is 50% faster than the TWINNY T
- › Easy to operate, thanks to hot-air technology



Uniroof 300

- › Reliable roof welding machine with a digital display
- › Low-maintenance drive motor
- › Excellent price-performance-ratio
- › Compact and light at only 17 kg (37.5 lbs)



Fusion 1

- › Double-sided rod intake
- › Extruder with integrated LED light
- › Attachable handle
- › Handheld extrusion welder
- › Slim and compact



Comet 500

- › Speeds up to 8 m/min (26.24 ft/min) without gearbox conversion
- › Automatic wedge positioning
- › High power-reserves
- › Large variety of pressure rollers and wedges
- › Force module to easily adjust the welding pressure



Uniplan 500

- › perfectly suited for overlap, hem and piping on various industrial fabrics.
- › Powerful hot-air blower with 18,000 rpm
- › Brushless blower motor
- › Automatic material lifting device



Examo 300

- › Ideal for shearing and peeling tests
- › Digital display for test parameters
- › Stably integrated in metal box
- › Tests according to DVS and ASTM standard



Minifloor

- › Converts to automatic welder when a heat gun is connected
- › Twice as fast as manual welding
- › Net weight of only 5.3 kg (11.7 lbs)
- › True to the groove thanks to the dual axis



LHS 61L System

- › Protection from overheating heating element and device
- › Remote control via analog interface
- › LED display (target/actual value display)
- › Continuously variable heating output adjustment via potentiometer






LEISTER TECHNOLOGIES AG

Galileo - Strasse 10
CH - 6056 Kaegiswil / Switzerland
leister@leister.com

 +41 41 662 74 74

 +41 41 662 74 16

GLOBAL SOURCE , RIYADH

Rail Center, Rail Street,
PO BOX 43269
Riyadh 11561

 +966 11 2048108 /09

 +966 11 2048110

GLOBAL SOURCE , JEDDAH

Behind Palestine Street,
PO BOX 112400
Jeddah 21371

 +966 12 2898592

 +966 12 2898572